

ZMA Series

Subminiature Snap-acting Switches



Features/Benefits

- **Reliable snap-acting mechanism**
- **Long electrical and mechanical life**
- **Compact size—Ideal when space is limited**
- **Various PCB terminals and actuators**
- **RoHS compatible & compliant**

Typical Applications

- **PCB detection switch**
- **Communication devices**
- **Testing equipment**
- **Security/Alarm systems**
- **Consumer electronics**



Specifications

CONTACT RATING: 3A @ 125 V AC 24 V DC
1 A @125 V AC 30 V DC
0.1A @ 125 V AC 60 V DC
ELECTRICAL LIFE: 300,000 cycles @ 0.1A / 10,000 cycles @ 3A.
MECHANICAL LIFE: 1,000,000 cycles.
INSULATION RESISTANCE: 100 M ohm min.
DIELECTRIC STRENGTH: 500 Vrms.
OPERATING TEMPERATURE: -40°C to +85°C
OPERATING FORCE: 80 or 150 grams.

* Low Level=conditions where no arcing occurs during switching, i.e., 0.4 VA max.
@ 20 V AC or DC max.

Materials

CASE/COVER: PBT
ACTUATOR: Nylon 6/6
MOVABLE CONTACTS: Silver.
STATIONARY CONTACTS: Silver.
TERMINALS: Brass, silver plated.

NOTE: Specifications and materials listed above are for switches with standard options.
For information on specific and custom switches, consult Customer Service Center.

Build-A-Switch

To order, simply select desired option from each category and place in the appropriate box. Available options are shown and described on pages J-37 and J-38. For additional options not shown in catalog, consult Customer Service Center.

Series	ZMA	SP, Mom.
Electrical Rating	00A	0.1A 125 V AC 48 V DC
	03A	3A 125 V AC 30 V DC
	01	1A 125 V AC 30 V DC
Operating Force	150	5.29 oz. / 150 grams
	080	2.82 oz. / 80 grams
Actuator	P00	Pin plunger
	S03	Simulated roller 5.8mm
	L30	Lever 20.5mm
	L11	Lever 7.2mm
	L08	Lever 3.95mm
	A03	Roller 1.3mm
	L04	Lever 3.9mm
	S06	Simulated roller 2.03mm
	S07	Simulated roller 0.75mm
Terminations	P	PC Thru-hole
	L	Left-footed, PC Thru-hole
	R	Right-footed, PC Thru-hole
	E	Solder
	K	PC Thru-hole with retention feature
	C	SPDT




Dimensions are shown: Inch (mm)
Specifications and dimensions subject to change

ZMA Series Subminiature Snap-acting Switches

SERIES **Z M** ■ ■ ■ ■ ■ ■ ■ ■

ZMA SUBMINIATURE SNAP-ACTING SWITCHES – SP MOMENTARY



ZMA03A150L04PC
SPDT

ELECTRICAL RATING ■ ■ ■ ■ ■ ■ ■ ■

OPTION CODE	CONTACT MATERIAL		ELECTRICAL RATING
	MOVABLE CONTACT	STATIONARY CONTACT	
00A	Silver plated	Silver plated	0.1 AMP @ 125 V AC 48 V DC
01	Fine silver	Fine silver	1 AMP @ 125 V AC 30 V DC
03A	Fine silver	Fine silver	3 AMPS @ 125 V AC 30 VDC

* Note: See Technical Data in section N of this catalog for RoHS compliant and compatible definition and specifications.
All models **C&K** with all options.
Consult Customer Service center for availability and delivery of nonstandard ratings.

OPERATING FORCE ■ ■ ■ ■ ■ ■ ■ ■

OPTION CODE	BASIC SWITCH OPERATING FORCE (OZ./GRAMS)
150	5.29 150
080	2.82 80



Third Angle
Projection
Dimensions are shown: Inches (mm)
Specifications and dimensions subject to change


Snap-acting

ZMA Series


Subminiature Snap-acting Switches

ACTUATOR


P00 PIN PLUNGER




L08 LEVER
3.95MM




S03 SIMULATED ROLLER
5.8MM




A03 ROLLER
1.3MM




L30 LEVER
20.5MM




L04 LEVER
3.9MM





L11 LEVER
7.2MM



S06 SIMULATED ROLLER
2.03MM



S07 SIMULATED ROLLER
0.75MM



Third Angle
Projection

Dimensions are shown: Inch (mm)
Specifications and dimensions subject to change


www.ck-components.com



ZMA Series Subminiature Snap-acting Switches


SWITCH CHARACTERISTICS

CODE	OPER. FORCE MAX. (GRAMS)		REL. FORCE MIN. (GRAMS)		'A' FP MAX. (MM)	'B' OP MAX. (MM)	'C' PT MAX. (MM)	'D' OT MIN. (MM)	'E' MIN. (MM)
P00	80	150	21	35	7.35	6.9 ±0.2	0.62	0.2	
S03	25	43	5	7	14.2	9.8 ±0.9	3.5	0.7	5.8
L30 (80gf)	13	21	2	3	16.8	9.5 ±1.9	6.9	0.55	20.5
L30 (150 gf)	13	21	2	3	16.8	9.5 1.9	6.9	0.55	20.5
L11	25	39	4	6	11.7	8.68 ±1	4.4	0.6	7.2
L08	27	48	3	8	13.5	10.75 ±0.8	3.5	0.3	3.95
A03	34	65	6	10	16.55	13.65 ±1	3.9	0.5	1.3
L04	30	50	5	8	10.1	7.9 ±0.8	3.0	0.6	3.9
S06	33	49	5	11	12.43	10.7 ±0.8	1.43	1.25	2.03
S07	40	65	2	5	13.0	9.7 ± 1	4.3	0.5	0.75




TERMINATIONS


P PC THRU-HOLE




L LEFT FOOTED, PC THRU-HOLE




R RIGHT FOOTED, PC THRU-HOLE



E SOLDER



K PC THRU-HOLE WITH RETENTION FEATURE



Dimensions are shown: Inches (mm)
Specifications and dimensions subject to change



Snap-acting

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

C&K Components:

[ZMA00A080L04RC](#) [ZMA00A080S06PC](#) [ZMA00A150L04PC](#) [ZMA00A150P00LC](#) [ZMA00A150P00PC](#)
[ZMA00A150P00RC](#) [ZMA00A150S06LC](#) [ZMA00A150S06PC](#) [ZMA03A150L04PC](#) [ZMA03A150P00LC](#)
[ZMA03A150P00PC](#) [ZMA03A150P00RC](#) [ZMA03A150S06PC](#)