


## Established Reliability Inductors

| Physical Parameters and Environmental Characteristics | ER1641               |                      |                      | ER1840               |                      | ER1537               |                      | ER1025                |                       |                       |
|-------------------------------------------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|-----------------------|-----------------------|-----------------------|
|                                                       | MIL-PRF-39010/01     | MIL-PRF-39010/02     | MIL-PRF-39010/03     | MIL-PRF-39010/04     | MIL-PRF-39010/05     | MIL-PRF-39010/06     | MIL-PRF-39010/07     | MIL-PRF-39010/08      | MIL-PRF-39010/09      | MIL-PRF-39010/10      |
| Inductance Range, $\mu\text{H}$                       | 0.10 to 0.82         | 0.91 to 12.0         | 15 to 1000           | 0.15 to 2.7          | 3.0 to 27.0          | 0.15 to 4.7          | 5.1 to 240.0         | 0.10 to 1.00          | 1.1 to 27.0           | 30 to 1000            |
| Core Material                                         | Phenolic             | Iron                 | Ferrite              | Phenolic             | Iron                 | Phenolic             | Iron                 | Phenolic              | Iron                  | Ferrite               |
| Sleeve                                                | Iron                 | Iron                 | Ferrite              | —                    | —                    | —                    | —                    | —                     | —                     | —                     |
| Length, Inches                                        | 0.410<br>$\pm 0.020$ | 0.410<br>$\pm 0.020$ | 0.410<br>$\pm 0.020$ | 0.437<br>$\pm 0.01$  | 0.437<br>$\pm 0.01$  | 0.375<br>$\pm 0.010$ | 0.375<br>$\pm 0.010$ | 0.250<br>$\pm 0.010$  | 0.250<br>$\pm 0.010$  | 0.250<br>$\pm 0.010$  |
| Millimeters                                           | 10.41<br>$\pm 0.51$  | 10.41<br>$\pm 0.51$  | 10.41<br>$\pm 0.51$  | 11.10<br>$\pm 0.25$  | 11.10<br>$\pm 0.25$  | 9.53<br>$\pm 0.25$   | 9.53<br>$\pm 0.25$   | 6.35<br>$\pm 0.25$    | 6.35<br>$\pm 0.25$    | 6.35<br>$\pm 0.25$    |
| Diameter, Inches                                      | 0.162<br>$\pm 0.010$ | 0.162<br>$\pm 0.010$ | 0.162<br>$\pm 0.010$ | 0.187<br>$\pm 0.010$ | 0.187<br>$\pm 0.010$ | 0.156<br>$\pm 0.010$ | 0.156<br>$\pm 0.010$ | 0.095<br>$\pm 0.010$  | 0.095<br>$\pm 0.010$  | 0.095<br>$\pm 0.010$  |
| Millimeters                                           | 4.11<br>$\pm 0.25$   | 4.11<br>$\pm 0.25$   | 4.11<br>$\pm 0.25$   | 4.75<br>$\pm 0.25$   | 4.75<br>$\pm 0.25$   | 3.96<br>$\pm 0.25$   | 3.96<br>$\pm 0.25$   | 2.41<br>$\pm 0.25$    | 2.41<br>$\pm 0.25$    | 2.41<br>$\pm 0.25$    |
| Lead Size — AWG #                                     | #22 TCW              | #22 TCW              | #22 TCW              | #22 TCW              | #22 TCW              | #22 TCW              | #22 TCW              | #24 TCW               | #24 TCW               | #24 TCW               |
| Inches                                                | 0.025<br>$\pm 0.002$ | 0.025<br>$\pm 0.002$ | 0.025<br>$\pm 0.002$ | 0.025<br>$\pm 0.002$ | 0.025<br>$\pm 0.002$ | 0.025<br>$\pm 0.002$ | 0.025<br>$\pm 0.002$ | 0.020<br>$\pm 0.0015$ | 0.020<br>$\pm 0.0015$ | 0.020<br>$\pm 0.0015$ |
| Millimeters                                           | 0.635<br>$\pm 0.051$ | 0.635<br>$\pm 0.051$ | 0.635<br>$\pm 0.051$ | 0.635<br>$\pm 0.051$ | 0.635<br>$\pm 0.051$ | 0.635<br>$\pm 0.051$ | 0.635<br>$\pm 0.051$ | 0.51<br>$\pm 0.04$    | 0.51<br>$\pm 0.04$    | 0.51<br>$\pm 0.04$    |
| Lead Length, Inches                                   | 1.438<br>$\pm 0.188$ | 1.438<br>$\pm 0.188$ | 1.438<br>$\pm 0.188$ | 1.438<br>$\pm 0.188$ | 1.438<br>$\pm 0.188$ | 1.438<br>$\pm 0.188$ | 1.438<br>$\pm 0.188$ | 1.438<br>$\pm 0.188$  | 1.438<br>$\pm 0.188$  | 1.438<br>$\pm 0.188$  |
| Millimeters                                           | 36.53<br>$\pm 4.77$  | 36.53<br>$\pm 4.77$  | 36.53<br>$\pm 4.77$  | 36.58<br>$\pm 3.05$  | 36.58<br>$\pm 3.05$  | 36.53<br>$\pm 4.77$  | 36.53<br>$\pm 4.77$  | 36.53<br>$\pm 4.77$   | 36.53<br>$\pm 4.77$   | 36.53<br>$\pm 4.77$   |
| Weight Max. (Grams)                                   | 0.85                 | 1.0                  | 1.0                  | 0.95                 | 0.95                 | 0.9                  | 0.9                  | 0.3                   | 0.3                   | 0.3                   |
| Current Rating at 90°C, Max. Rise °C                  | 15                   | 15                   | 15                   | 35                   | 15                   | 35                   | 15                   | 35                    | 15                    | 15                    |
| Operating Temp. °C                                    | -55 to +105          | -55 to +105          | -55 to +105          | -55 to +125          | -55 to +105          | -55 to +125          | -55 to +105          | -55 to +125           | -55 to +105           | -55 to +105           |
| Max. Power Dissipation at 90°C, Watts                 | 0.11                 | 0.11                 | 0.11                 | 0.385                | 0.385                | 0.312                | 0.134                | 0.21                  | 0.09                  | 0.073                 |
| Coupling                                              | 3% Max.              | 3% Max.              | 3% Max.              | —                    | —                    | —                    | —                    | —                     | —                     | —                     |
| Body Color                                            | Black                | Black                | Black                | Tan                  | Tan                  | Tan                  | Tan                  | Tan                   | Tan                   | Tan                   |

## MARKING EXAMPLE &amp; ORDERING INFORMATION



**MIL-PRF-39010 Molded RF Coils** with Sn10 high-temperature solder for internal connections.

**Approved Through Failure Rate Level S**

**Note** The complete Military dash numbers will include two additional letters, indicated in the tables on the following three pages by \*\*. The first additional letter will indicate tolerance: J indicates  $\pm 5\%$ ; K indicates  $\pm 10\%$ ; L indicates  $\pm 20\%$ .

The second letter will indicate the failure rate (e.g., M, P, R, S).

**Packaging** Tape & reel

ER1025: 12" reel, 3500 pieces max.; 14" reel, 6000 pieces max.  
ER1537 and ER1641: 12" reel, 2500 pieces max.; 14" reel, 4000 pieces max.  
ER1840: 12" reel, 2500 pieces max.; 14" reel, 3000 pieces max. For additional packaging options, see technical section.

**Made in the U.S.A.**

CONTINUED ON NEXT PAGE

## ER SERIES (continued)

| DELEVAN PART NUMBER | DASH NUMBER | MILITARY | INDUCTANCE (μH) | IND. TOLERANCE (%) | TEST FREQUENCY (MHz) | Q MINIMUM | SRF MINIMUM (MHz) | DC RESISTANCE (OHMS @ 25°C) | CURRENT (mA) | RATED DC |
|---------------------|-------------|----------|-----------------|--------------------|----------------------|-----------|-------------------|-----------------------------|--------------|----------|
| MIL-PRF-39010/01    |             |          |                 |                    |                      |           |                   |                             |              |          |
| ER1641-101**        | AR10**      | 0.10     | 5.10            | 50                 | 25.0                 | 250       | 0.025             | 1,790                       |              |          |
| ER1641-111**        | AR11**      | 0.11     | 5               | 50                 | 25.0                 | 250       | 0.034             | 1,530                       |              |          |
| ER1641-121**        | AR12**      | 0.12     | 5.10            | 50                 | 25.0                 | 250       | 0.034             | 1,530                       |              |          |
| ER1641-131**        | AR13**      | 0.13     | 5               | 50                 | 25.0                 | 250       | 0.037             | 1,470                       |              |          |
| ER1641-151**        | AR15**      | 0.15     | 5.10            | 50                 | 25.0                 | 250       | 0.037             | 1,470                       |              |          |
| ER1641-161**        | AR16**      | 0.16     | 5               | 50                 | 25.0                 | 250       | 0.047             | 1,300                       |              |          |
| ER1641-181**        | AR18**      | 0.18     | 5.10            | 50                 | 25.0                 | 250       | 0.047             | 1,300                       |              |          |
| ER1641-201**        | AR20**      | 0.20     | 5               | 49                 | 25.0                 | 250       | 0.067             | 1,100                       |              |          |
| ER1641-221**        | AR22**      | 0.22     | 5.10            | 49                 | 25.0                 | 250       | 0.067             | 1,100                       |              |          |
| ER1641-241**        | AR24**      | 0.24     | 5               | 47                 | 25.0                 | 250       | 0.110             | 853                         |              |          |
| ER1641-271**        | AR27**      | 0.27     | 5.10            | 47                 | 25.0                 | 250       | 0.110             | 853                         |              |          |
| ER1641-301**        | AR30**      | 0.30     | 5               | 46                 | 25.0                 | 250       | 0.130             | 780                         |              |          |
| ER1641-331**        | AR33**      | 0.33     | 5.10            | 46                 | 25.0                 | 250       | 0.130             | 780                         |              |          |
| ER1641-361**        | AR36**      | 0.36     | 5               | 44                 | 25.0                 | 250       | 0.180             | 670                         |              |          |
| ER1641-391**        | AR39**      | 0.39     | 5.10            | 44                 | 25.0                 | 250       | 0.180             | 670                         |              |          |
| ER1641-431**        | AR43**      | 0.43     | 5               | 44                 | 25.0                 | 235       | 0.250             | 565                         |              |          |
| ER1641-471**        | AR47**      | 0.47     | 5.10            | 44                 | 25.0                 | 235       | 0.250             | 565                         |              |          |
| ER1641-511**        | AR51**      | 0.51     | 5               | 43                 | 25.0                 | 210       | 0.330             | 490                         |              |          |
| ER1641-561**        | AR56**      | 0.56     | 5.10            | 43                 | 25.0                 | 210       | 0.330             | 490                         |              |          |
| ER1641-621**        | AR62**      | 0.62     | 5               | 42                 | 25.0                 | 190       | 0.450             | 420                         |              |          |
| ER1641-681**        | AR68**      | 0.68     | 5.10            | 42                 | 25.0                 | 190       | 0.450             | 420                         |              |          |
| ER1641-751**        | AR75**      | 0.75     | 5               | 40                 | 25.0                 | 180       | 0.590             | 370                         |              |          |
| ER1641-821**        | AR82**      | 0.82     | 5.10            | 40                 | 25.0                 | 180       | 0.590             | 370                         |              |          |
| MIL-PRF-39010/02    |             |          |                 |                    |                      |           |                   |                             |              |          |
| ER1641-911**        | AR91**      | 0.91     | 5               | 44                 | 25.0                 | 140       | 0.070             | 1,070                       |              |          |
| ER1641-102**        | A1R0**      | 1.00     | 5.10            | 44                 | 25.0                 | 140       | 0.070             | 1,070                       |              |          |
| ER1641-112**        | A1R1**      | 1.10     | 5               | 44                 | 7.9                  | 130       | 0.100             | 895                         |              |          |
| ER1641-122**        | A1R2**      | 1.20     | 5.10            | 44                 | 7.9                  | 130       | 0.100             | 895                         |              |          |
| ER1641-132**        | A1R3**      | 1.30     | 5               | 44                 | 7.9                  | 115       | 0.120             | 815                         |              |          |
| ER1641-152**        | A1R5**      | 1.50     | 5.10            | 44                 | 7.9                  | 115       | 0.120             | 815                         |              |          |
| ER1641-162**        | A1R6**      | 1.60     | 5               | 44                 | 7.9                  | 105       | 0.140             | 755                         |              |          |
| ER1641-182**        | A1R8**      | 1.80     | 5.10            | 44                 | 7.9                  | 105       | 0.140             | 755                         |              |          |
| ER1641-202**        | A2R0**      | 2.00     | 5               | 44                 | 7.9                  | 100       | 0.190             | 650                         |              |          |
| ER1641-222**        | A2R2**      | 2.20     | 5.10            | 44                 | 7.9                  | 100       | 0.190             | 650                         |              |          |
| ER1641-242**        | A2R4**      | 2.40     | 5               | 44                 | 7.9                  | 92        | 0.280             | 535                         |              |          |
| ER1641-272**        | A2R7**      | 2.70     | 5.10            | 44                 | 7.9                  | 92        | 0.280             | 535                         |              |          |
| ER1641-302**        | A3R0**      | 3.00     | 5               | 44                 | 7.9                  | 85        | 0.350             | 480                         |              |          |
| ER1641-332**        | A3R3**      | 3.30     | 5.10            | 44                 | 7.9                  | 85        | 0.350             | 480                         |              |          |
| ER1641-362**        | A3R6**      | 3.60     | 5               | 44                 | 7.9                  | 75        | 0.400             | 450                         |              |          |
| ER1641-392**        | A3R9**      | 3.90     | 5.10            | 44                 | 7.9                  | 75        | 0.400             | 450                         |              |          |
| ER1641-432**        | A4R3**      | 4.30     | 5               | 44                 | 7.9                  | 70        | 0.550             | 380                         |              |          |
| ER1641-472**        | A4R7**      | 4.70     | 5.10            | 44                 | 7.9                  | 70        | 0.550             | 380                         |              |          |
| ER1641-512**        | A5R1**      | 5.10     | 5               | 44                 | 7.9                  | 65        | 0.720             | 335                         |              |          |
| ER1641-562**        | A5R6**      | 5.60     | 5.10            | 44                 | 7.9                  | 65        | 0.720             | 335                         |              |          |
| ER1641-622**        | A6R2**      | 6.20     | 5               | 44                 | 7.9                  | 55        | 1.020             | 280                         |              |          |
| ER1641-682**        | A6R8**      | 6.80     | 5.10            | 50                 | 7.9                  | 55        | 1.020             | 280                         |              |          |
| ER1641-752**        | A7R5**      | 7.50     | 5               | 50                 | 7.9                  | 50        | 1.320             | 245                         |              |          |
| ER1641-822**        | A8R2**      | 8.20     | 5.10            | 50                 | 7.9                  | 50        | 1.320             | 245                         |              |          |
| ER1641-912**        | A9R1**      | 9.10     | 5               | 50                 | 7.9                  | 46        | 1.620             | 220                         |              |          |
| ER1641-103**        | A100**      | 10.00    | 5.10            | 50                 | 7.9                  | 46        | 1.620             | 220                         |              |          |
| ER1641-113**        | A110**      | 11.00    | 5               | 50                 | 2.5                  | 44        | 2.000             | 200                         |              |          |
| ER1641-123**        | A120**      | 12.00    | 5.10            | 50                 | 2.5                  | 44        | 2.000             | 200                         |              |          |
| MIL-PRF-39010/03    |             |          |                 |                    |                      |           |                   |                             |              |          |
| ER1641-153**        | A150**      | 15       | 5.10            | 45                 | 2.50                 | 49.0      | 0.80              | 315                         |              |          |
| ER1641-163**        | A160**      | 16       | 5               | 45                 | 2.50                 | 45.0      | 0.89              | 300                         |              |          |
| ER1641-183**        | A180**      | 18       | 5.10            | 45                 | 2.50                 | 45.0      | 0.89              | 300                         |              |          |
| ER1641-203**        | A200**      | 20       | 5               | 45                 | 2.50                 | 41.0      | 0.96              | 290                         |              |          |
| ER1641-223**        | A220**      | 22       | 5.10            | 45                 | 2.50                 | 41.0      | 0.96              | 290                         |              |          |
| ER1641-243**        | A240**      | 24       | 5               | 45                 | 2.50                 | 38.0      | 1.19              | 260                         |              |          |
| ER1641-273**        | A270**      | 27       | 5.10            | 45                 | 2.50                 | 38.0      | 1.19              | 260                         |              |          |
| ER1641-303**        | A300**      | 30       | 5               | 45                 | 2.50                 | 34.0      | 1.37              | 240                         |              |          |
| ER1641-333**        | A330**      | 33       | 5.10            | 45                 | 2.50                 | 34.0      | 1.37              | 240                         |              |          |
| ER1641-363**        | A360**      | 36       | 5               | 45                 | 2.50                 | 29.0      | 1.93              | 205                         |              |          |
| ER1641-393**        | A390**      | 39       | 5.10            | 50                 | 2.50                 | 29.0      | 1.93              | 205                         |              |          |
| ER1641-433**        | A430**      | 43       | 5               | 50                 | 2.50                 | 27.0      | 2.11              | 195                         |              |          |
| ER1641-473**        | A470**      | 47       | 5.10            | 50                 | 2.50                 | 27.0      | 2.11              | 195                         |              |          |
| ER1641-513**        | A510**      | 51       | 5               | 50                 | 2.50                 | 25.0      | 2.23              | 190                         |              |          |
| ER1641-563**        | A560**      | 56       | 5.10            | 50                 | 2.50                 | 25.0      | 2.23              | 190                         |              |          |

| MIL-PRF-39010/03 (continued) |        |       |         |    |      |      |       |       |
|------------------------------|--------|-------|---------|----|------|------|-------|-------|
| ER1641-623**                 | A620** | 62    | 5       | 50 | 2.50 | 21.0 | 2.44  | 180   |
| ER1641-683**                 | A680** | 68    | 5,10    | 50 | 2.50 | 21.0 | 2.44  | 180   |
| ER1641-753**                 | A750** | 75    | 5       | 50 | 2.50 | 10.5 | 2.70  | 170   |
| ER1641-823**                 | A820** | 82    | 5,10    | 50 | 2.50 | 10.5 | 2.70  | 170   |
| ER1641-913**                 | A910** | 91    | 5       | 50 | 2.50 | 10.0 | 3.12  | 160   |
| ER1641-104**                 | A101** | 100   | 5,10    | 50 | 2.50 | 10.0 | 3.12  | 160   |
| ER1641-114**                 | A111** | 110   | 5       | 50 | 0.79 | 9.7  | 3.60  | 150   |
| ER1641-124**                 | A121** | 120   | 5,10    | 55 | 0.79 | 9.7  | 3.60  | 150   |
| ER1641-134**                 | A131** | 130   | 5       | 55 | 0.79 | 8.5  | 4.10  | 140   |
| ER1641-154**                 | A151** | 150   | 5,10    | 55 | 0.79 | 8.5  | 4.10  | 140   |
| ER1641-164**                 | A161** | 160   | 5       | 55 | 0.79 | 8.0  | 4.40  | 135   |
| ER1641-184**                 | A181** | 180   | 5,10    | 55 | 0.79 | 8.0  | 4.40  | 135   |
| ER1641-204**                 | A201** | 200   | 5       | 55 | 0.79 | 7.5  | 5.00  | 125   |
| ER1641-224**                 | A221** | 220   | 5,10    | 55 | 0.79 | 7.5  | 5.00  | 125   |
| ER1641-244**                 | A241** | 240   | 5       | 55 | 0.79 | 7.0  | 5.80  | 115   |
| ER1641-274**                 | A271** | 270   | 5,10    | 55 | 0.79 | 7.0  | 5.80  | 115   |
| ER1641-304**                 | A301** | 300   | 5       | 55 | 0.79 | 6.5  | 6.40  | 110   |
| ER1641-334**                 | A331** | 330   | 5,10    | 55 | 0.79 | 6.5  | 6.40  | 110   |
| ER1641-364**                 | A361** | 360   | 5       | 55 | 0.79 | 6.2  | 7.40  | 105   |
| ER1641-394**                 | A391** | 390   | 5,10    | 60 | 0.79 | 6.2  | 7.40  | 105   |
| ER1641-434**                 | A431** | 430   | 5       | 60 | 0.79 | 5.7  | 9.50  | 92    |
| ER1641-474**                 | A471** | 470   | 5,10    | 60 | 0.79 | 5.7  | 9.50  | 92    |
| ER1641-514**                 | A511** | 510   | 5       | 60 | 0.79 | 4.7  | 10.50 | 90    |
| ER1641-564**                 | A561** | 560   | 5,10    | 60 | 0.79 | 4.7  | 10.50 | 90    |
| ER1641-624**                 | A621** | 620   | 5       | 60 | 0.79 | 4.5  | 11.80 | 80    |
| ER1641-684**                 | A681** | 680   | 5,10    | 60 | 0.79 | 4.5  | 11.80 | 80    |
| ER1641-754**                 | A751** | 750   | 5       | 60 | 0.79 | 4.2  | 13.00 | 80    |
| ER1641-824**                 | A821** | 820   | 5,10    | 60 | 0.79 | 4.2  | 13.00 | 80    |
| ER1641-914**                 | A911** | 910   | 5       | 60 | 0.79 | 3.8  | 17.50 | 70    |
| ER1641-105**                 | A102** | 1,000 | 5,10    | 60 | 0.79 | 3.8  | 17.50 | 70    |
| MIL-PRF-39010/04             |        |       |         |    |      |      |       |       |
| ER1840-00**                  | BR15** | 0.15  | 5,10,20 | 55 | 25.0 | 510  | 0.030 | 2,900 |
| ER1840-101**                 | BR16** | 0.16  | 5       | 50 | 25.0 | 415  | 0.035 | 2,700 |
| ER1840-01**                  | BR18** | 0.18  | 5,10    | 50 | 25.0 | 415  | 0.035 | 2,700 |
| ER1840-102**                 | BR20** | 0.20  | 5       | 50 | 25.0 | 415  | 0.035 | 2,700 |
| ER1840-02**                  | BR22** | 0.22  | 5,10,20 | 50 | 25.0 | 415  | 0.035 | 2,700 |
| ER1840-103**                 | BR24** | 0.24  | 5       | 50 | 25.0 | 350  | 0.065 | 2,000 |
| ER1840-03**                  | BR27** | 0.27  | 5,10    | 50 | 25.0 | 350  | 0.065 | 2,000 |
| ER1840-104**                 | BR30** | 0.30  | 5       | 50 | 25.0 | 350  | 0.065 | 2,000 |
| ER1840-04**                  | BR33** | 0.33  | 5,10,20 | 50 | 25.0 | 350  | 0.065 | 2,000 |
| ER1840-105**                 | BR36** | 0.36  | 5       | 50 | 25.0 | 300  | 0.085 | 1,700 |
| ER1840-05**                  | BR39** | 0.39  | 5,10    | 50 | 25.0 | 300  | 0.085 | 1,700 |
| ER1840-106**                 | BR43** | 0.43  | 5       | 50 | 25.0 | 300  | 0.085 | 1,700 |
| ER1840-06**                  | BR47** | 0.47  | 5,10,20 | 50 | 25.0 | 300  | 0.085 | 1,700 |
| ER1840-107**                 | BR51** | 0.51  | 5       | 50 | 25.0 | 270  | 0.125 | 1,450 |
| ER1840-07**                  | BR56** | 0.56  | 5,10    | 50 | 25.0 | 270  | 0.125 | 1,450 |
| ER1840-108**                 | BR62** | 0.62  | 5       | 45 | 25.0 | 250  | 0.150 | 1,300 |
| ER1840-08**                  | BR68** | 0.68  | 5,10    | 45 | 25.0 | 250  | 0.150 | 1,300 |
| ER1840-109**                 | BR75** | 0.75  | 5       | 40 | 25.0 | 210  | 0.205 | 1,100 |
| ER1840-09**                  | BR82** | 0.82  | 5,10    | 40 | 25.0 | 210  | 0.205 | 1,100 |
| ER1840-110**                 | BR91** | 0.91  | 5       | 40 | 25.0 | 200  | 0.290 | 930   |
| ER1840-10**                  | B1R0** | 1.00  | 5,10    | 40 | 25.0 | 200  | 0.290 | 930   |
| ER1840-111**                 | B1R1** | 1.10  | 5       | 30 | 7.9  | 180  | 0.400 | 785   |
| ER1840-11**                  | B1R2** | 1.20  | 5,10    | 30 | 7.9  | 180  | 0.400 | 785   |
| ER1840-112**                 | B1R3** | 1.30  | 5       | 30 | 7.9  | 170  | 0.485 | 720   |
| ER1840-12**                  | B1R5** | 1.50  | 5,10    | 30 | 7.9  | 170  | 0.485 | 720   |
| ER1840-113**                 | B1R6** | 1.60  | 5       | 30 | 7.9  | 150  | 0.740 | 580   |
| ER1840-13**                  | B1R8** | 1.80  | 5,10    | 30 | 7.9  | 150  | 0.740 | 580   |
| ER1840-114**                 | B2R0** | 2.00  | 5       | 30 | 7.9  | 140  | 0.970 | 505   |
| ER1840-14**                  | B2R2** | 2.20  | 5,10    | 30 | 7.9  | 140  | 0.970 | 505   |
| ER1840-15**                  | B2R4** | 2.40  | 5       | 30 | 7.9  | 120  | 1.200 | 460   |
| ER1840-16**                  | B2R7** | 2.70  | 5,10    | 30 | 7.9  | 120  | 1.200 | 460   |



## ER SERIES (continued)

| DELEVAN PART NUMBER | DASH NUMBER | MILITARY | INDUCTANCE (μH) | IND. TOLERANCE (%) | TEST FREQUENCY (MHz) | Q MINIMUM | SRF MINIMUM (MHz) | MAXIMUM (OHMS @ 25°C) | DC RESISTANCE (mΩ @ 25°C) | CURRENT (mA) | RATED DC |
|---------------------|-------------|----------|-----------------|--------------------|----------------------|-----------|-------------------|-----------------------|---------------------------|--------------|----------|
| MIL-PRF-39010/05    |             |          |                 |                    |                      |           |                   |                       |                           |              |          |
| ER1840-17**         | A3R0**      |          | 3.00            | 5                  | 30                   | 7.9       | 70                | 0.140                 | 945                       |              |          |
| ER1840-18**         | A3R3**      |          | 3.30            | 5,10               | 30                   | 7.9       | 70                | 0.140                 | 945                       |              |          |
| ER1840-19**         | A3R6**      |          | 3.60            | 5                  | 30                   | 7.9       | 65                | 0.155                 | 870                       |              |          |
| ER1840-20**         | A3R9**      |          | 3.90            | 5,10               | 30                   | 7.9       | 65                | 0.155                 | 870                       |              |          |
| ER1840-21**         | A4R3**      |          | 4.30            | 5                  | 30                   | 7.9       | 60                | 0.210                 | 745                       |              |          |
| ER1840-22**         | A4R7**      |          | 4.70            | 5,10               | 30                   | 7.9       | 60                | 0.210                 | 745                       |              |          |
| ER1840-23**         | A5R1**      |          | 5.10            | 5                  | 30                   | 7.9       | 50                | 0.280                 | 645                       |              |          |
| ER1840-24**         | A5R6**      |          | 5.60            | 5,10               | 30                   | 7.9       | 50                | 0.280                 | 645                       |              |          |
| ER1840-25**         | A6R2**      |          | 6.20            | 5                  | 30                   | 7.9       | 50                | 0.375                 | 560                       |              |          |
| ER1840-26**         | A6R8**      |          | 6.80            | 5,10               | 30                   | 7.9       | 50                | 0.375                 | 560                       |              |          |
| ER1840-27**         | A7R5**      |          | 7.50            | 5                  | 30                   | 7.9       | 48                | 0.440                 | 520                       |              |          |
| ER1840-28**         | A8R2**      |          | 8.20            | 5,10               | 30                   | 7.9       | 48                | 0.440                 | 520                       |              |          |
| ER1840-29**         | A9R1**      |          | 9.10            | 5                  | 30                   | 7.9       | 42                | 0.605                 | 440                       |              |          |
| ER1840-30**         | A100**      |          | 10.0            | 5,10               | 30                   | 7.9       | 42                | 0.605                 | 440                       |              |          |
| ER1840-31**         | A110**      |          | 11.0            | 5                  | 30                   | 2.5       | 36                | 1.05                  | 335                       |              |          |
| ER1840-32**         | A120**      |          | 12.0            | 5,10               | 50                   | 2.5       | 36                | 1.05                  | 335                       |              |          |
| ER1840-33**         | A130**      |          | 13.0            | 5                  | 50                   | 2.5       | 30                | 1.20                  | 310                       |              |          |
| ER1840-34**         | A150**      |          | 15.0            | 5,10               | 55                   | 2.5       | 30                | 1.20                  | 310                       |              |          |
| ER1840-135**        | A160**      |          | 16.0            | 5                  | 55                   | 2.5       | 30                | 1.95                  | 245                       |              |          |
| ER1840-35**         | A180**      |          | 18.0            | 5,10               | 60                   | 2.5       | 30                | 1.95                  | 245                       |              |          |
| ER1840-136**        | A200**      |          | 20.0            | 5                  | 60                   | 2.5       | 24                | 2.20                  | 230                       |              |          |
| ER1840-36**         | A220**      |          | 22.0            | 5,10               | 60                   | 2.5       | 24                | 2.20                  | 230                       |              |          |
| ER1840-37**         | A240**      |          | 24.0            | 5                  | 60                   | 2.5       | 22                | 2.75                  | 205                       |              |          |
| ER1840-38**         | A270**      |          | 27.0            | 5,10               | 65                   | 2.5       | 22                | 2.75                  | 205                       |              |          |
| MIL-PRF-39010/06    |             |          |                 |                    |                      |           |                   |                       |                           |              |          |
| ER1537-00**         | BR15**      |          | 0.15            | 5,10,20            | 50                   | 25.0      | 525               | 0.030                 | 2,450                     |              |          |
| ER1537-101**        | BR16**      |          | 0.16            | 5                  | 50                   | 25.0      | 460               | 0.055                 | 1,810                     |              |          |
| ER1537-01**         | BR18**      |          | 0.18            | 5,10               | 50                   | 25.0      | 460               | 0.055                 | 1,810                     |              |          |
| ER1537-102**        | BR20**      |          | 0.20            | 5                  | 50                   | 25.0      | 460               | 0.055                 | 1,810                     |              |          |
| ER1537-02**         | BR22**      |          | 0.22            | 5,10,20            | 50                   | 25.0      | 460               | 0.055                 | 1,810                     |              |          |
| ER1537-103**        | BR24**      |          | 0.24            | 5                  | 45                   | 25.0      | 360               | 0.090                 | 1,400                     |              |          |
| ER1537-03**         | BR27**      |          | 0.27            | 5,10               | 45                   | 25.0      | 360               | 0.090                 | 1,400                     |              |          |
| ER1537-104**        | BR30**      |          | 0.30            | 5                  | 45                   | 25.0      | 360               | 0.090                 | 1,400                     |              |          |
| ER1537-04**         | BR33**      |          | 0.33            | 5,10,20            | 45                   | 25.0      | 360               | 0.090                 | 1,400                     |              |          |
| ER1537-105**        | BR36**      |          | 0.36            | 5                  | 45                   | 25.0      | 310               | 0.12                  | 1,225                     |              |          |
| ER1537-05**         | BR39**      |          | 0.39            | 5,10               | 45                   | 25.0      | 310               | 0.12                  | 1,225                     |              |          |
| ER1537-106**        | BR43**      |          | 0.43            | 5                  | 45                   | 25.0      | 310               | 0.12                  | 1,225                     |              |          |
| ER1537-06**         | BR47**      |          | 0.47            | 5,10,20            | 45                   | 25.0      | 310               | 0.12                  | 1,225                     |              |          |
| ER1537-107**        | BR51**      |          | 0.51            | 5                  | 45                   | 25.0      | 280               | 0.135                 | 1,150                     |              |          |
| ER1537-07**         | BR56**      |          | 0.56            | 5,10               | 50                   | 25.0      | 280               | 0.135                 | 1,150                     |              |          |
| ER1537-108**        | BR62**      |          | 0.62            | 5                  | 50                   | 25.0      | 250               | 0.150                 | 1,100                     |              |          |
| ER1537-08**         | BR68**      |          | 0.68            | 5,10               | 50                   | 25.0      | 250               | 0.150                 | 1,100                     |              |          |
| ER1537-09**         | BR75**      |          | 0.75            | 5                  | 50                   | 25.0      | 220               | 0.220                 | 900                       |              |          |
| ER1537-10**         | BR82**      |          | 0.82            | 5,10               | 50                   | 25.0      | 220               | 0.220                 | 900                       |              |          |
| ER1537-11**         | BR91**      |          | 0.91            | 5                  | 50                   | 25.0      | 200               | 0.290                 | 785                       |              |          |
| ER1537-12**         | B1R0**      |          | 1.00            | 5,10               | 50                   | 25.0      | 200               | 0.290                 | 785                       |              |          |
| ER1537-13**         | B1R1**      |          | 1.10            | 5                  | 33                   | 7.9       | 180               | 0.420                 | 650                       |              |          |
| ER1537-14**         | B1R2**      |          | 1.20            | 5,10               | 33                   | 7.9       | 180               | 0.420                 | 650                       |              |          |
| ER1537-15**         | B1R3**      |          | 1.30            | 5                  | 33                   | 7.9       | 160               | 0.500                 | 600                       |              |          |
| ER1537-16**         | B1R5**      |          | 1.50            | 5,10               | 33                   | 7.9       | 160               | 0.500                 | 600                       |              |          |
| ER1537-17**         | B1R6**      |          | 1.60            | 5                  | 33                   | 7.9       | 150               | 0.650                 | 525                       |              |          |
| ER1537-18**         | B1R8**      |          | 1.80            | 5,10               | 33                   | 7.9       | 150               | 0.650                 | 525                       |              |          |
| ER1537-19**         | B2R0**      |          | 2.00            | 5                  | 33                   | 7.9       | 135               | 0.950                 | 435                       |              |          |
| ER1537-20**         | B2R2**      |          | 2.20            | 5,10               | 33                   | 7.9       | 135               | 0.950                 | 435                       |              |          |
| ER1537-21**         | B2R4**      |          | 2.40            | 5                  | 33                   | 7.9       | 120               | 1.20                  | 385                       |              |          |
| ER1537-22**         | B2R7**      |          | 2.70            | 5,10               | 33                   | 7.9       | 120               | 1.20                  | 385                       |              |          |
| ER1537-23**         | B3R0**      |          | 3.00            | 5                  | 33                   | 7.9       | 110               | 2.00                  | 300                       |              |          |
| ER1537-24**         | B3R3**      |          | 3.30            | 5,10               | 33                   | 7.9       | 110               | 2.00                  | 300                       |              |          |
| ER1537-25**         | B3R6**      |          | 3.60            | 5                  | 33                   | 7.9       | 100               | 2.30                  | 280                       |              |          |
| ER1537-26**         | B3R9**      |          | 3.90            | 5,10               | 33                   | 7.9       | 100               | 2.30                  | 280                       |              |          |
| ER1537-27**         | B4R3**      |          | 4.30            | 5                  | 33                   | 7.9       | 90                | 2.60                  | 260                       |              |          |
| ER1537-28**         | B4R7**      |          | 4.70            | 5,10               | 33                   | 7.9       | 90                | 2.60                  | 260                       |              |          |

| VAN PART<br>NUMBER | DASH NUMBER | MILITARY<br>INDUCTANCE | IND. TOLERANCE (μH) | TEST FREQUENCY (MHz) | Q MINIMUM | SRF MINIMUM (MHz) | MAXIMUM (OHMS @ 25°C) | DC RESISTANCE (mΩ @ 25°C) | CURRENT (mA) | RATED DC |
|--------------------|-------------|------------------------|---------------------|----------------------|-----------|-------------------|-----------------------|---------------------------|--------------|----------|
|                    |             |                        |                     |                      |           |                   |                       |                           |              |          |
| MIL-PRF-39010/07   |             |                        |                     |                      |           |                   |                       |                           |              |          |
| ER1537-29**        | A5R1**      | 5.1                    | 5                   | 45                   | 7.90      | 60.0              | 0.32                  | 495                       |              |          |
| ER1537-30**        | A5R6**      | 5.6                    | 5,10                | 45                   | 7.90      | 60.0              | 0.32                  | 495                       |              |          |
| ER1537-31**        | A6R2**      | 6.2                    | 5                   | 45                   | 7.90      | 55.0              | 0.50                  | 395                       |              |          |
| ER1537-32**        | A6R8**      | 6.8                    | 5,10                | 50                   | 7.90      | 55.0              | 0.50                  | 395                       |              |          |
| ER1537-33**        | A7R5**      | 7.5                    | 5                   | 50                   | 7.90      | 50.0              | 0.60                  | 360                       |              |          |
| ER1537-34**        | A8R2**      | 8.2                    | 5,10                | 50                   | 7.90      | 50.0              | 0.60                  | 360                       |              |          |
| ER1537-35**        | A9R1**      | 9.1                    | 5                   | 50                   | 7.90      | 45.0              | 0.90                  | 290                       |              |          |
| ER1537-36**        | A100**      | 10.0                   | 5,10                | 55                   | 7.90      | 45.0              | 0.90                  | 290                       |              |          |
| ER1537-37**        | A110**      | 11.0                   | 5                   | 55                   | 2.50      | 42.0              | 1.10                  | 265                       |              |          |
| ER1537-38**        | A120**      | 12.0                   | 5,10                | 65                   | 2.50      | 42.0              | 1.10                  | 265                       |              |          |
| ER1537-39**        | A130**      | 13.0                   | 5                   | 65                   | 2.50      | 40.0              | 1.40                  | 240                       |              |          |
| ER1537-40**        | A150**      | 15.0                   | 5,10                | 65                   | 2.50      | 40.0              | 1.40                  | 240                       |              |          |
| ER1537-41**        | A160**      | 16.0                   | 5                   | 65                   | 2.50      | 34.0              | 2.25                  | 185                       |              |          |
| ER1537-42**        | A180**      | 18.0                   | 5,10                | 75                   | 2.50      | 34.0              | 2.25                  | 185                       |              |          |
| ER1537-43**        | A200**      | 20.0                   | 5                   | 75                   | 2.50      | 30.0              | 2.50                  | 175                       |              |          |
| ER1537-44**        | A220**      | 22.0                   | 5,10                | 75                   | 2.50      | 30.0              | 2.50                  | 175                       |              |          |
| ER1537-46**        | A240**      | 24.0                   | 5                   | 60                   | 2.50      | 25.0              | 2.60                  | 170                       |              |          |
| ER1537-48**        | A270**      | 27.0                   | 5,10                | 60                   | 2.50      | 25.0              | 2.60                  | 170                       |              |          |
| ER1537-50**        | A300**      | 30.0                   | 5                   | 60                   | 2.50      | 19.0              | 3.00                  | 165                       |              |          |
| ER1537-52**        | A330**      | 33.0                   | 5,10                | 65                   | 2.50      | 19.0              | 3.00                  | 165                       |              |          |
| ER1537-54**        | A360**      | 36.0                   | 5                   | 60                   | 2.50      | 15.5              | 2.50                  | 180                       |              |          |
| ER1537-56**        | A390**      | 39.0                   | 5                   | 60                   | 2.50      | 14.5              | 2.60                  | 176                       |              |          |
| ER1537-58**        | A430**      | 43.0                   | 5                   | 60                   | 2.50      | 13.7              | 2.70                  | 172                       |              |          |
| ER1537-60**        | A470**      | 47.0                   | 5                   | 55                   | 2.50      | 13.0              | 2.75                  | 170                       |              |          |
| ER1537-62**        | A510**      | 51.0                   | 5                   | 55                   | 2.50      | 12.7              | 2.85                  | 167                       |              |          |
| ER1537-64**        | A560**      | 56.0                   | 5                   | 55                   | 2.50      | 12.0              | 3.00                  | 164                       |              |          |
| ER1537-66**        | A620**      | 62.0                   | 5                   | 55                   | 2.50      | 11.5              | 3.15                  | 160                       |              |          |
| ER1537-68**        | A680**      | 68.0                   | 5                   | 55                   | 2.50      | 11.0              | 3.30                  | 156                       |              |          |
| ER1537-70**        | A750**      | 75.0                   | 5                   | 55                   | 2.50      | 10.5              | 3.70                  | 147                       |              |          |
| ER1537-72**        | A820**      | 82.0                   | 5                   | 50                   | 2.50      | 10.3              | 3.90                  | 143                       |              |          |
| ER1537-74**        | A910**      | 91.0                   | 5                   | 50                   | 2.50      | 10.0              | 4.30                  | 136                       |              |          |
| ER1537-76**        | A101**      | 100.0                  | 5                   | 50                   | 2.50      | 9.50              | 4.50                  | 133                       |              |          |
| ER1537-78**        | A111**      | 110.0                  | 5                   | 60                   | 0.79      | 8.90              | 4.90                  | 128                       |              |          |
| ER1537-80**        | A121**      | 120.0                  | 5                   | 65                   | 0.79      | 8.70              | 5.20                  | 124                       |              |          |
| ER1537-82**        | A131**      | 130.0                  | 5                   | 65                   | 0.79      | 8.50              | 5.45                  | 121                       |              |          |
| ER1537-84**        | A151**      | 150.0                  | 5                   | 65                   | 0.79      | 8.00              | 6.05                  | 114                       |              |          |
| ER1537-86**        | A161**      | 160.0                  | 5                   | 65                   | 0.79      | 7.50              | 6.40                  | 111                       |              |          |
| ER1537-88**        | A181**      | 180.0                  | 5                   | 65                   | 0.79      | 7.00              | 6.75                  | 108                       |              |          |
| ER1537-90**        | A201**      | 200.0                  | 5                   | 65                   | 0.79      | 6.50              | 7.10                  | 106                       |              |          |
| ER1537-92**        | A221**      | 220.0                  | 5                   | 65                   | 0.79      | 6.20              | 7.45                  | 103                       |              |          |
| ER1537-94**        | A241**      | 240.0                  | 5                   | 65                   | 0.79      | 5.90              | 7.80                  | 101                       |              |          |
| MIL-PRF-39010/08   |             |                        |                     |                      |           |                   |                       |                           |              |          |
| ER1025-94**        | BR10**      | 0.10                   | 5,10                | 40                   | 25.0      | 680               | 0.08                  | 1,350                     |              |          |
| ER1025-95**        | BR11**      | 0.11                   | 5                   | 40                   | 25.0      | 640               | 0.09                  | 1,270                     |              |          |
| ER1025-96**        | BR12**      | 0.12                   | 5,10                | 40                   | 25.0      | 640               | 0.09                  | 1,270                     |              |          |
| ER1025-97**        | BR13**      | 0.13                   | 5                   | 38                   | 25.0      | 600               | 0.10                  | 1,200                     |              |          |
| ER1025-00**        | BR15**      | 0.15                   | 5,10                | 38                   | 25.0      | 600               | 0.10                  | 1,200                     |              |          |
| ER1025-01**        | BR16**      | 0.16                   | 5                   | 35                   | 25.0      | 550               | 0.12                  | 1,105                     |              |          |
| ER1025-02**        | BR18**      | 0.18                   | 5,10                | 35                   | 25.0      | 550               | 0.12                  | 1,105                     |              |          |
| ER1025-03**        | BR20**      | 0.20                   | 5                   | 33                   | 25.0      | 510               | 0.14                  | 1,025                     |              |          |
| ER1025-04**        | BR22**      | 0.22                   | 5,10                | 33                   | 25.0      | 510               | 0.14                  | 1,025                     |              |          |
| ER1025-05**        | BR24**      | 0.24                   | 5                   | 33                   | 25.0      | 430               | 0.16                  | 960                       |              |          |
| ER1025-06**        | BR27**      | 0.27                   | 5,10                | 33                   | 25.0      | 430               | 0.16                  | 960                       |              |          |
| ER1025-07**        | BR30**      | 0.30                   | 5                   | 30                   | 25.0      | 410               | 0.22                  | 815                       |              |          |
| ER1025-08**        | BR33**      | 0.33                   | 5,10                | 30                   | 25.0      | 410               | 0.22                  | 815                       |              |          |
| ER1025-09**        | BR36**      | 0.36                   | 5                   | 30                   | 25.0      | 365               | 0.30                  | 700                       |              |          |
| ER1025-10**        | BR39**      | 0.39                   | 5,10                | 30                   | 25.0      | 365               | 0.30                  | 700                       |              |          |
| ER1025-11**        | BR43**      | 0.43                   | 5                   | 30                   | 25.0      | 330               | 0.35                  | 650                       |              |          |
| ER1025-12**        | BR47**      | 0.47                   | 5,10                | 30                   | 25.0      | 330               | 0.35                  | 650                       |              |          |
| ER1025-13**        | BR51**      | 0.51                   | 5                   | 30                   | 25.0      | 300               | 0.50                  | 545                       |              |          |
| ER1025-14**        | BR56**      | 0.56                   | 5,10                | 30                   | 25.0      | 300               | 0.50                  | 545                       |              |          |
| ER1025-15**        | BR62**      | 0.62                   | 5                   | 28                   | 25.0      | 275               | 0.60                  | 495                       |              |          |
| ER1025-16**        | BR68**      | 0.68                   | 5,10                | 28                   | 25.0      | 275               | 0.60                  | 495                       |              |          |
| ER1025-17**        | BR75**      | 0.75                   | 5                   | 28                   | 25.0      | 250               | 0.85                  | 415                       |              |          |
| ER1025-18**        | BR82**      | 0.82                   | 5,10                | 28                   | 25.0      | 250               | 0.85                  | 415                       |              |          |
| ER1025-19**        | BR91**      | 0.91                   | 5                   | 25                   | 25.0      | 230               | 1.00                  | 385                       |              |          |
| ER1025-20**        | B1R0**      | 1.00                   | 5,10                | 25                   | 25.0      | 230               | 1.00                  | 385                       |              |          |

## ER SERIES (continued)

| DELEVAN PART NUMBER | DASH NUMBER | MILITARY | INDUCTANCE (μH) | IND. TOLERANCE (%) | TEST FREQUENCY (MHz) | SRF MINIMUM (MHz) | MAXIMUM (OHMS @ 25°C) | DC RESISTANCE (OHMS @ 25°C) | CURRENT (mA) | RATED DC |
|---------------------|-------------|----------|-----------------|--------------------|----------------------|-------------------|-----------------------|-----------------------------|--------------|----------|
| MIL-PRF-39010/09    |             |          |                 |                    |                      |                   |                       |                             |              |          |
| ER1025-21**         | A1R1**      | 1.1      | 5               | 25                 | 7.9                  | 150               | 0.18                  | 590                         |              |          |
| ER1025-22**         | A1R2**      | 1.2      | 5,10            | 25                 | 7.9                  | 150               | 0.18                  | 590                         |              |          |
| ER1025-23**         | A1R3**      | 1.3      | 5               | 25                 | 7.9                  | 140               | 0.22                  | 535                         |              |          |
| ER1025-24**         | A1R5**      | 1.5      | 5,10            | 28                 | 7.9                  | 140               | 0.22                  | 535                         |              |          |
| ER1025-25**         | A1R6**      | 1.6      | 5               | 28                 | 7.9                  | 125               | 0.30                  | 455                         |              |          |
| ER1025-26**         | A1R8**      | 1.8      | 5,10            | 30                 | 7.9                  | 125               | 0.30                  | 455                         |              |          |
| ER1025-27**         | A2R0**      | 2.0      | 5               | 30                 | 7.9                  | 115               | 0.40                  | 395                         |              |          |
| ER1025-28**         | A2R2**      | 2.2      | 5,10            | 30                 | 7.9                  | 115               | 0.40                  | 395                         |              |          |
| ER1025-29**         | A2R4**      | 2.4      | 5               | 30                 | 7.9                  | 100               | 0.55                  | 335                         |              |          |
| ER1025-30**         | A2R7**      | 2.7      | 5,10            | 37                 | 7.9                  | 100               | 0.55                  | 335                         |              |          |
| ER1025-31**         | A3R0**      | 3.0      | 5               | 37                 | 7.9                  | 90                | 0.85                  | 270                         |              |          |
| ER1025-32**         | A3R3**      | 3.3      | 5,10            | 45                 | 7.9                  | 90                | 0.85                  | 270                         |              |          |
| ER1025-33**         | A3R6**      | 3.6      | 5               | 45                 | 7.9                  | 80                | 1.00                  | 250                         |              |          |
| ER1025-34**         | A3R9**      | 3.9      | 5,10            | 45                 | 7.9                  | 80                | 1.00                  | 250                         |              |          |
| ER1025-35**         | A4R3**      | 4.3      | 5               | 45                 | 7.9                  | 75                | 1.20                  | 230                         |              |          |
| ER1025-36**         | A4R7**      | 4.7      | 5,10            | 45                 | 7.9                  | 75                | 1.20                  | 230                         |              |          |
| ER1025-37**         | A5R1**      | 5.1      | 5               | 45                 | 7.9                  | 65                | 1.80                  | 185                         |              |          |
| ER1025-38**         | A5R6**      | 5.6      | 5,10            | 50                 | 7.9                  | 65                | 1.80                  | 185                         |              |          |
| ER1025-39**         | A6R2**      | 6.2      | 5               | 50                 | 7.9                  | 60                | 2.00                  | 175                         |              |          |
| ER1025-40**         | A6R8**      | 6.8      | 5,10            | 50                 | 7.9                  | 60                | 2.00                  | 175                         |              |          |
| ER1025-41**         | A7R5**      | 7.5      | 5               | 50                 | 7.9                  | 55                | 2.70                  | 155                         |              |          |
| ER1025-42**         | A8R2**      | 8.2      | 5,10            | 55                 | 7.9                  | 55                | 2.70                  | 155                         |              |          |
| ER1025-43**         | A9R1**      | 9.1      | 5               | 55                 | 7.9                  | 50                | 3.70                  | 130                         |              |          |
| ER1025-44**         | A100**      | 10.0     | 5,10            | 55                 | 7.9                  | 50                | 3.70                  | 130                         |              |          |
| ER1025-45**         | A110**      | 11.0     | 5               | 45                 | 2.5                  | 40                | 2.70                  | 130                         |              |          |
| ER1025-46**         | A120**      | 12.0     | 5,10            | 45                 | 2.5                  | 40                | 2.70                  | 155                         |              |          |
| ER1025-47**         | A130**      | 13.0     | 5               | 40                 | 2.5                  | 35                | 2.80                  | 150                         |              |          |
| ER1025-48**         | A150**      | 15.0     | 5,10            | 40                 | 2.5                  | 35                | 2.80                  | 150                         |              |          |
| ER1025-49**         | A160**      | 16.0     | 5               | 40                 | 2.5                  | 30                | 3.10                  | 145                         |              |          |
| ER1025-50**         | A180**      | 18.0     | 5,10            | 50                 | 2.5                  | 30                | 3.10                  | 145                         |              |          |
| ER1025-51**         | A200**      | 20.0     | 5               | 50                 | 2.5                  | 25                | 3.30                  | 140                         |              |          |
| ER1025-52**         | A220**      | 22.0     | 5,10            | 50                 | 2.5                  | 25                | 3.30                  | 140                         |              |          |
| ER1025-53**         | A240**      | 24.0     | 5               | 50                 | 2.5                  | 20                | 3.50                  | 135                         |              |          |
| ER1025-54**         | A270**      | 27.0     | 5,10            | 50                 | 2.5                  | 20                | 3.50                  | 135                         |              |          |

| DELEVAN PART NUMBER | DASH NUMBER | MILITARY | INDUCTANCE (μH) | IND. TOLERANCE (%) | TEST FREQUENCY (MHz) | SRF MINIMUM (MHz) | MAXIMUM (OHMS @ 25°C) | DC RESISTANCE (OHMS @ 25°C) | CURRENT (mA) | RATED DC |
|---------------------|-------------|----------|-----------------|--------------------|----------------------|-------------------|-----------------------|-----------------------------|--------------|----------|
| MIL-PRF-39010/10    |             |          |                 |                    |                      |                   |                       |                             |              |          |
| ER1025-55**         | A300**      | 30.0     | 5               | 45                 | 2.50                 | 24                | 3.4                   | 130                         |              |          |
| ER1025-56**         | A330**      | 33.0     | 5,10            | 45                 | 2.50                 | 24                | 3.4                   | 130                         |              |          |
| ER1025-57**         | A360**      | 36.0     | 5               | 45                 | 2.50                 | 22                | 3.6                   | 125                         |              |          |
| ER1025-58**         | A390**      | 39.0     | 5,10            | 45                 | 2.50                 | 22                | 3.6                   | 125                         |              |          |
| ER1025-59**         | A430**      | 43.0     | 5               | 45                 | 2.50                 | 20                | 4.5                   | 110                         |              |          |
| ER1025-60**         | A470**      | 47.0     | 5,10            | 45                 | 2.50                 | 20                | 4.5                   | 110                         |              |          |
| ER1025-61**         | A510**      | 51.0     | 5               | 45                 | 2.50                 | 18                | 5.7                   | 100                         |              |          |
| ER1025-62**         | A560**      | 56.0     | 5,10            | 45                 | 2.50                 | 18                | 5.7                   | 100                         |              |          |
| ER1025-63**         | A620**      | 62.0     | 5               | 45                 | 2.50                 | 15                | 6.7                   | 92                          |              |          |
| ER1025-64**         | A680**      | 68.0     | 5,10            | 50                 | 2.50                 | 15                | 6.7                   | 92                          |              |          |
| ER1025-65**         | A750**      | 75.0     | 5               | 50                 | 2.50                 | 14                | 7.3                   | 88                          |              |          |
| ER1025-66**         | A820**      | 82.0     | 5,10            | 50                 | 2.50                 | 14                | 7.3                   | 88                          |              |          |
| ER1025-67**         | A910**      | 91.0     | 5               | 50                 | 2.50                 | 13                | 8.0                   | 84                          |              |          |
| ER1025-68**         | A101**      | 100      | 5,10            | 50                 | 2.50                 | 13                | 8.0                   | 84                          |              |          |
| ER1025-69**         | A111**      | 110      | 5               | 30                 | 0.79                 | 12                | 13.0                  | 66                          |              |          |
| ER1025-70**         | A121**      | 120      | 5,10            | 30                 | 0.79                 | 12                | 13.0                  | 66                          |              |          |
| ER1025-71**         | A131**      | 130      | 5               | 30                 | 0.79                 | 11                | 15.0                  | 61                          |              |          |
| ER1025-72**         | A151**      | 150      | 5,10            | 30                 | 0.79                 | 11                | 15.0                  | 61                          |              |          |
| ER1025-73**         | A161**      | 160      | 5               | 30                 | 0.79                 | 10                | 17.0                  | 57                          |              |          |
| ER1025-74**         | A181**      | 180      | 5,10            | 30                 | 0.79                 | 10                | 17.0                  | 57                          |              |          |
| ER1025-75**         | A201**      | 200      | 5               | 30                 | 0.79                 | 9.0               | 21.0                  | 52                          |              |          |
| ER1025-76**         | A221**      | 220      | 5,10            | 30                 | 0.79                 | 9.0               | 21.0                  | 52                          |              |          |
| ER1025-77**         | A241**      | 240      | 5               | 30                 | 0.79                 | 8.0               | 25.0                  | 47                          |              |          |
| ER1025-78**         | A271**      | 270      | 5,10            | 30                 | 0.79                 | 8.0               | 25.0                  | 47                          |              |          |
| ER1025-79**         | A301**      | 300      | 5               | 30                 | 0.79                 | 7.0               | 28.0                  | 45                          |              |          |
| ER1025-80**         | A331**      | 330      | 5,10            | 30                 | 0.79                 | 7.0               | 28.0                  | 45                          |              |          |
| ER1025-81**         | A361**      | 360      | 5               | 30                 | 0.79                 | 6.5               | 35.0                  | 40                          |              |          |
| ER1025-82**         | A391**      | 390      | 5,10            | 30                 | 0.79                 | 6.5               | 35.0                  | 40                          |              |          |
| ER1025-83**         | A431**      | 430      | 5               | 30                 | 0.79                 | 6.0               | 42.0                  | 36                          |              |          |
| ER1025-84**         | A471**      | 470      | 5,10            | 30                 | 0.79                 | 6.0               | 42.0                  | 36                          |              |          |
| ER1025-85**         | A511**      | 510      | 5               | 30                 | 0.79                 | 5.0               | 46.0                  | 35                          |              |          |
| ER1025-86**         | A561**      | 560      | 5,10            | 30                 | 0.79                 | 5.0               | 46.0                  | 35                          |              |          |
| ER1025-87**         | A621**      | 620      | 5               | 30                 | 0.79                 | 4.0               | 60.0                  | 30                          |              |          |
| ER1025-88**         | A681**      | 680      | 5,10            | 30                 | 0.79                 | 4.0               | 60.0                  | 30                          |              |          |
| ER1025-89**         | A751**      | 750      | 5               | 30                 | 0.79                 | 3.8               | 65.0                  | 29                          |              |          |
| ER1025-90**         | A821**      | 820      | 5,10            | 30                 | 0.79                 | 3.8               | 65.0                  | 29                          |              |          |
| ER1025-91**         | A911**      | 910      | 5               | 30                 | 0.79                 | 3.4               | 72.0                  | 28                          |              |          |
| ER1025-92**         | A102**      | 1,000    | 5,10            | 30                 | 0.79                 | 3.4               | 72.0                  | 28                          |              |          |

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## API Delevan:

[ER1840-00KR](#) [ER1840-00LR](#) [ER1840-101JR](#) [ER1840-01KR](#) [ER1840-102JR](#) [ER1840-02KR](#) [ER1840-02LR](#)  
[ER1840-103JR](#) [ER1840-03KR](#) [ER1840-104JR](#) [ER1840-04KR](#) [ER1840-04LR](#) [ER1840-105JR](#) [ER1840-05KR](#)  
[ER1840-106JR](#) [ER1840-06KR](#) [ER1840-06LR](#) [ER1840-107JR](#) [ER1840-07KR](#) [ER1840-108JR](#) [ER1840-08KR](#)  
[ER1840-109JR](#) [ER1840-09KR](#) [ER1840-110JR](#) [ER1840-10KR](#) [ER1840-111JR](#) [ER1840-11KR](#) [ER1840-112JR](#)  
[ER1840-12KR](#) [ER1840-113JR](#) [ER1840-13KR](#) [ER1840-114JR](#) [ER1840-14KR](#) [ER1840-15JR](#) [ER1840-16KR](#)  
[ER1840-17JR](#) [ER1840-18KR](#) [ER1840-19JR](#) [ER1840-20KR](#) [ER1840-21JR](#) [ER1840-22KR](#) [ER1840-23JR](#) [ER1840-24KR](#)  
[ER1840-25JR](#) [ER1840-26KR](#) [ER1840-27JR](#) [ER1840-28KR](#) [ER1840-29JR](#) [ER1840-30KR](#) [ER1840-31JR](#)  
[ER1840-32KR](#) [ER1840-33JR](#) [ER1840-34KR](#) [ER1840-135JR](#) [ER1840-35KR](#) [ER1840-136JR](#) [ER1840-36KR](#)  
[ER1840-37JR](#) [ER1840-38KR](#) [ER1840-00JR](#) [ER1840-01JR](#) [ER1840-02JR](#) [ER1840-03JR](#) [ER1840-04JR](#) [ER1840-05JR](#)  
[ER1840-06JR](#) [ER1840-07JR](#) [ER1840-08JR](#) [ER1840-09JR](#) [ER1840-10JR](#) [ER1840-11JR](#) [ER1840-12JR](#)  
[ER1840-13JR](#) [ER1840-14JR](#) [ER1840-16JR](#) [ER1840-18JR](#) [ER1840-20JR](#) [ER1840-22JR](#) [ER1840-24JR](#) [ER1840-26JR](#)  
[ER1840-28JR](#) [ER1840-30JR](#) [ER1840-32JR](#) [ER1840-34JR](#) [ER1840-35JR](#) [ER1840-36JR](#) [ER1840-38JR](#)  
[ER1840-00JM](#) [ER1840-00KM](#) [ER1840-00LM](#) [ER1840-101JM](#) [ER1840-01JM](#) [ER1840-01KM](#) [ER1840-102JM](#)  
[ER1840-02JM](#) [ER1840-02KM](#) [ER1840-02LM](#) [ER1840-103JM](#) [ER1840-03JM](#) [ER1840-03KM](#)