




Shielded High SRF Inductors – 0805PS



- Higher SRF and than our other power inductors
- High inductance with tight tolerance
- Excellent current handling for a part this size

Designer's Kit C348 contains 6 of each part

Core material Ceramic/Ferrite

Core and winding loss See www.coilcraft.com/coreloss

Terminations RoHS compliant silver-palladium-platinum-glass frit.

Weight 57.6– 62.4 mg

Ambient temperature –40°C to +65°C with Irms current, +65°C to +105°C with derated current

Storage temperature Component: –40°C to +105°C.

Tape and reel packaging: –40°C to +80°C

Resistance to soldering heat Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

Moisture Sensitivity Level (MSL) 1 (unlimited floor life at <30°C / 85% relative humidity)

Failures in Time (FIT) / Mean Time Between Failures (MTBF)

38 per billion hours / 26,315,789 hours, calculated per Telcordia SR-332

Packaging 1500/7" reel; 7500/13" reel Plastic tape: 8 mm wide, 0.23 mm thick, 4 mm pocket spacing, 2.34 mm pocket depth

PCB washing Tested with pure water or alcohol only. For other solvents, see Doc787_PCB_Washing.pdf.

Part number ¹	L ² ±10% (µH)	Q min ³ at 1 MHz	DCR ⁴ max (Ohms)	SRF ⁵ typ (MHz)	Isat ⁶ (A)	Irms ⁷ (A)
0805PS-102KL	1.0	21	0.14	340	0.90	1.6
0805PS-152KL	1.5	21	0.18	265	0.85	1.3
0805PS-272KL	2.7	21	0.35	190	0.60	0.88
0805PS-332KL	3.3	21	0.50	180	0.55	0.70
0805PS-392KL	3.9	21	0.74	165	0.50	0.61
0805PS-472KL	4.7	21	0.85	155	0.43	0.59
0805PS-562KL	5.6	21	0.91	143	0.38	0.57
0805PS-682KL	6.8	21	1.37	118	0.32	0.46
0805PS-103KL	10	21	1.51	66	0.27	0.43
0805PS-153KL	15	21	2.04	34	0.22	0.34
0805PS-223KL	22	25	2.48	22	0.18	0.33
0805PS-333KL	33	25	3.00	17	0.16	0.28
0805PS-473KL	47	25	3.85	15	0.15	0.26
0805PS-683KL	68	28	4.42	12	0.12	0.24
0805PS-823KL	82	30	6.00	12	0.11	0.21
0805PS-104KL	100	32	6.96	9.0	0.10	0.19
0805PS-124KL	120	32	7.51	7.7	0.10	0.18
0805PS-154KL	150	32	8.33	5.0	0.08	0.18
0805PS-224KL	220	32	13.71	5.0	0.07	0.14
0805PS-334KL	330	32	20.53	3.5	0.06	0.11

1. When ordering, please specify **packaging** code:

0805PS-334KLC

Packaging: **C** = 7" machine-ready reel. EIA-481 embossed plastic tape (1500 parts per full reel).

B = Less than full reel. In tape, but not machine ready. To have a leader and trailer added (\$25 charge), use code letter C instead.

D = 13" machine-ready reel. EIA-481 embossed plastic tape. Factory order only, not stocked (7500 parts per full reel).

2. Inductance measured at 100 kHz, 0.1 Vrms, using a Coilcraft SMD-A fixture in Agilent/HP 4263B LCR meter.

3. Q measured on an Agilent/HP 4291 with an Agilent/HP 16193 test fixture.

4. DCR measured on a micro-ohmmeter and a Coilcraft CCF840 test fixture.

5. SRF measured using an Agilent/HP 8753D network analyzer and a Coilcraft SMD-D test fixture.

6. DC current at which the inductance drops 10% (typ) from its value without current.

7. Current that causes a 40°C temperature rise from 25°C ambient.

8. Electrical specifications at 25°C.

Refer to Doc 362 "Soldering Surface Mount Components" before soldering.



www.coilcraft.com

US +1-847-639-6400 sales@coilcraft.com

UK +44-1236-730595 sales@coilcraft-europe.com

Taiwan +886-2-2264 3646 sales@coilcraft.com.tw

China +86-21-6218 8074 sales@coilcraft.com.cn

Singapore + 65-6484 8412 sales@coilcraft.com.sg

COILCRAFT ACCURATE
PRECISION REPEATABLE
MEASUREMENTS
SEE WEB SITE **TEST FIXTURES**

Document 265-1 Revised 03/14/12



© Coilcraft Inc. 2013

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.





Power Chip Inductors - 0805PS Series

Typical L vs Frequency Typical L vs Current




Typical Q vs Frequency



A	B	C	D	E	F	G	H	I	J	
max	max	max								inches
0.133	0.118	0.079	0.053	0.080	0.050	0.020	0.070	0.040	0.030	
3,38	3,00	2,00	1,35	2,03	1,27	0,51	1,78	1,02	0,76	mm

Irms Derating



www.coilcraft.com

US +1-847-639-6400 sales@coilcraft.com
UK +44-1236-730595 sales@coilcraft-europe.com
Taiwan +886-2-2264 3646 sales@coilcraft.com.tw
China +86-21-6218 8074 sales@coilcraft.com.cn
Singapore + 65-6484 8412 sales@coilcraft.com.sg

Document 265-2 Revised 03/14/12

© Coilcraft Inc. 2013

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Coilcraft:

[0805PS-823KLB](#) [0805PS-332KLB](#) [0805PS-154KLC](#) [0805PS-102KLC](#) [0805PS-124KLC](#) [0805PS-104KLB](#) [0805PS-103KLB](#) [0805PS-152KLB](#) [0805PS-334KLB](#) [0805PS-223KLC](#) [0805PS-154KLB](#) [0805PS-224KLB](#) [0805PS-272KLB](#) [0805PS-392KLB](#) [0805PS-333KLB](#) [0805PS-102KLB](#) [0805PS-153KLC](#) [0805PS-683KLB](#) [0805PS-472KLC](#) [0805PS-473KLC](#) [0805PS-223KLB](#) [0805PS-682KLC](#) [0805PS-683KLC](#) [0805PS-334KLC](#) [0805PS-152KLC](#) [0805PS-472KLB](#) [0805PS-224KLC](#) [0805PS-392KLC](#) [0805PS-333KLC](#) [0805PS-272KLC](#) [0805PS-153KLB](#) [0805PS-473KLB](#) [0805PS-332KLC](#) [0805PS-562KLB](#) [0805PS-124KLB](#) [0805PS-104KLC](#) [0805PS-103KLC](#) [0805PS-823KLC](#) [0805PS-562KLC](#) [0805PS-682KLB](#)