


max. 79 m³/h

DC axial fans

Series 8400 N 80 x 80 x 25 mm





Highlights:

- Ball bearings and sleeve bearings available.
- Some models suitable for use at high ambient temperatures up to 85 °C.

General characteristics:

- Material: fibreglass-reinforced plastic. Impeller PA, housing PBT.
- Fully integrated electronic commutation.
- Protected against reverse polarity and locking.
- Connection via single strands AWG 24, TR 64. Bared and tin-plated.
- Air exhaust over struts. Direction of rotation counter-clockwise, seen on rotor.
- Mass: 95 g.

Nominal data		Air flow	Air flow	Nominal voltage	Voltage range	Sound pressure level	Sound power level	Sinter sleeve bearings	Ball bearings	Power input	Nominal speed	Temperature range	Service life L ₁₀ (40 °C)	Service life L ₁₀ (T _{max})	Life expectancy L ₁₀ Δ	Curve	Specials
Type		m³/h	CFM	VDC	VDC	dB(A)	Bel(A)	□ / ■		Watts	RPM	°C	Hours	Hours	Hours		P. 110/112
8412 NGLE		33	19,4	12	8...15	12	3,5	□		0,5	1 500	-20...+85	80 000 / 27 500	160 000	160 000	1	/2
8412 NLE		33	19,4	12	8...15	17	3,7	■		0,3	1 500	-20...+85	80 000 / 27 500	160 000	160 000	1	
8412 NGMLE		45	26,5	12	8...15	19	3,9	□		0,9	2 050	-20...+80	80 000 / 32 500	160 000	160 000	2	
8412 NMLE		45	26,5	12	8...15	21	4,0	■		0,6	2 050	-20...+85	80 000 / 27 500	160 000	160 000	2	
8412 NGME		58	34,1	12	8...15	26	4,3	□		1,4	2 600	-20...+75	80 000 / 35 000	160 000	160 000	3	/2
8412 NME		58	34,1	12	8...15	27	4,4	■		1,0	2 600	-20...+75	80 000 / 35 000	160 000	160 000	3	
8412 NG		69	40,6	12	8...15	32	4,7	□		2,0	3 100	-20...+70	70 000 / 35 000	140 000	140 000	4	/2
8412 N		69	40,6	12	8...15	32	4,7	■		2,0	3 100	-20...+70	70 000 / 35 000	140 000	140 000	4	/2
8412 NH		79	46,5	12	8...13,2	37	5,0	■		2,2	3 600	-20...+70	70 000 / 35 000	140 000	140 000	5	/2/12
8412 NH-217		79	46,5	12	8...15	37	5,0	■		2,4	3 600	-20...+70	70 000 / 35 000	140 000	140 000	5	
8414 NGL		33	19,4	24	18...28	12	3,5	□		0,7	1 500	-20...+70	80 000 / 40 000	160 000	160 000	1	/2
8414 NL		33	19,4	24	18...28	17	3,7	■		0,7	1 500	-20...+70	80 000 / 40 000	160 000	160 000	1	
8414 NGML		45	26,5	24	18...28	19	3,9	□		1,1	2 050	-20...+70	80 000 / 40 000	160 000	160 000	2	
8414 NML		45	26,5	24	18...28	21	4,0	■		1,1	2 050	-20...+70	80 000 / 40 000	160 000	160 000	2	
8414 NGM		58	34,1	24	18...28	26	4,3	□		1,4	2 600	-20...+70	80 000 / 40 000	160 000	160 000	3	/2
8414 NM		58	34,1	24	18...28	27	4,4	■		1,4	2 600	-20...+70	80 000 / 40 000	160 000	160 000	3	
8414 NG		69	40,6	24	18...28	32	4,7	□		2,0	3 100	-20...+70	70 000 / 35 000	140 000	140 000	4	/2
8414 N		69	40,6	24	18...28	32	4,7	■		2,0	3 100	-20...+70	70 000 / 35 000	140 000	140 000	4	/2
8414 NH		79	46,5	24	18...26	37	5,0	■		2,4	3 600	-20...+70	70 000 / 35 000	140 000	140 000	5	/2
8414 NH-221		79	46,5	24	18...28	37	5,0	■		2,4	3 600	-20...+70	70 000 / 35 000	140 000	140 000	5	
8418 N		69	40,6	48	36...56	32	4,7	■		2,0	3 100	-20...+70	70 000 / 35 000	140 000	140 000	4	



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ebm-papst:](#)

[8412N](#) [8412NMLE](#) [8412NG](#) [8412NGH](#) [8412NH](#) [8414N](#) [8414NG](#) [8414NGL](#) [8414NGM](#) [8414NGML](#) [8414NH](#)
[8414NL](#) [8414NM](#) [8414NML](#)