
ELED ST Receptacle

EDR-S-30B-X-SSTX-XX



Features

- 1300nm or 1550nm Wavelength
- High Optical Power
- High Operating Current
- High Operating Temperature
- Low Modal Noise
- For Single-mode use
- ST-A and ST-B Receptacle Package
- For Datacom or Measurement Applications
- RoHS Compliant available

Absolute Maximum Ratings (Tc=25°C)

Parameter	Symbol	Condition	Rating	Unit
Reverse Voltage	V_r	CW	2.5	V
Forward Current	I_f	CW	150	mA
Operating Temperature	T_{opr}	-	-20 ~ 70	°C
Storage Temperature	T_{stg}	-	-40 ~ 85	°C

(All optical data refer to a coupled 9/125μm SM fiber)

Optical and Electrical Characteristics 1300nm (Tc=25°C)


Parameter	Symbol	Min	Typ	Max	Unit	Test Conditions
Wavelength	λ	1260	1300	1340	nm	CW
Spectral Width	Δλ	30	-	80	nm	CW(FWHM)
Operating Current	I_{op}	-	40	60	mA	CW
Output Power L M H	P_O	 10 20 30	 - - -	 - - -	μW	CW at Iop=40mA
Spectral Ripple		-	-	10	%	λ±10nm
Foward Voltage	Vf	-	1.2	2.0	V	CW
Rise Time	T_r	-	1.5	-	ns	
Fall Time	T_f	-	2.5	-	ns	
Output Power Variation		-	4	-	dB	25°C to +70°C

20550 Nordhoff St. • Chatsworth, CA 91311 • tel: 818.773.9044 • fax: 818.576.9486
9F, No 81, Shui Lee Rd. • Hsinchu, Taiwan, R.O.C. • tel: 886.3.5169222 • fax: 886.3.5169213


LUMNDS704-JAN2006
rev. A.4

Pin Assignment **Units in mm.**


Receptacle Package Style : ST – A Type



Receptacle Package Style : ST – B Type



Pinout-3 Pin



Ordering Information

EDR-S-30B-X-SSTX-XX

- **Family**: EDR=ELED Receptacle
- **Device**: S=Short
- **Wavelength**: 30:1300nm
- **Tolerance**: B=+/- 40nm
- **Power**: L/M/H
- **Fiber**: S=Single Mode
- **Connector**: ST
- **Package Option**: A=ST-A, B=ST-B
- **RoHS Compliant**: -/G5/GR
  - Blank = RoHS non-compliant product
  - G5 = RoHS 5/6-compliant product (lead exemption)
  - GR = Full RoHS compliant product (no exemption)

Warnings

Handling Precautions: This device is susceptible to damage as a result of electrostatic discharge (ESD). A static free environment is highly recommended. Follow guidelines according to proper ESD procedures.
Laser Safety: Radiation emitted by laser devices can be dangerous to human eyes. Avoid eye exposure to direct or indirect radiation.

Legal Notice

IMPORTANT NOTICE!
All information contained in this document is subject to change without notice, at Luminent's sole and absolute discretion. Luminent warrants performance of its products to current specifications only in accordance with the company's standard one-year warranty; however, specifications designated as "preliminary" are given to describe components only, and Luminent expressly disclaims any and all warranties for said products, including express, implied, and statutory warranties, warranties of merchantability, fitness for a particular purpose, and non-infringement of proprietary rights. Please refer to the company's Terms and Conditions of Sale for further warranty information.

Luminent assumes no liability for applications assistance, customer product design, software performance, or infringement of patents, services, or intellectual property described herein. No license, either express or implied, is granted under any patent right, copyright, or intellectual property right, and Luminent makes no representations or warranties that the product(s) described herein are free from patent, copyright, or intellectual property rights. Products described in this document are NOT intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. Luminent customers using or selling products for use in such applications do so at their own risk and agree to fully defend and indemnify Luminent for any damages resulting from such use or sale.

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROVIDED ON AN "AS IS" BASIS. Customer agrees that Luminent is not liable for any actual, consequential, exemplary, or other damages arising directly or indirectly from any use of the information contained in this document. Customer must contact Luminent to obtain the latest version of this publication to verify, before placing any order, that the information contained herein is current.

© Luminent, Inc. 2006
All rights reserved