
# MALLORY Mallory Sonalert Products,Inc. Part #: MSR516NJR Sales Outline Drawing Revision: E

Specifications:

Sound Level Category	Loud
Mode of Operation	Slow Pulse @ 0.5 - 2.5 PPS
Voltage Rating	5 to 16 VDC
Frequency	3700 ± 500 Hz
Loudness @ 1 FT	88 to 96 dB(A) Typ.
Current Draw	3-12 mA
Housing Material	Valox (UL94V-0), Color Blue
Storage Temperature	-40° to +85° C
Operating Temperature	-40° to +85° C
Weight (Typical)	3.5g
Options	Please contact factory.

Dimensions: Inches (mm) ROHS Compliant



NOTE A: TERMINALS - .031" DIA. NICKEL/TIN COATED BRASS.

NOTE B:
MOUNTING- INSERT INTO PRINTED CIRCUIT BOARD AND HAND OR MACHINE SOLDER.
UNITS ARE SUITABLE FOR WAVE SOLDERING. RECOMMENDED MAXIMUM TEMPERATURE
AND TIME DURATION FOR WAVE SOLDERING IS +270°C AND 3 SECONDS RESPECTIVELY.

## MALLORY SONALERT PRODUCTS, INC.

#### **MSR & MSO Series Buzzers**

#### **Aqueous Wash:**

In order to process MSR & MSO Series buzzers through an aqueous wash, the buzzer must have a wash label and be sealed on the back with epoxy. Sealed buzzers have a "SR" suffix in the part number. For example, P/N MSR320SR is sealed and appropriate for aqueous wash. P/N MSR320R is not sealed.

After aqueous wash, the wash label must be removed from the buzzer.

#### **Wave Solder Profile:**

Refer to the wave solder machine manufacturer's recommended wave solder profile. If needed, adjust the maximum time & temperature to 270°C for 3 seconds to process MSR & MSO series buzzers.

Moisture Sensitivity Level (MSL): Level 1 (Unlimited)

Packaging: All parts are bulk packed.

Origin: Made in USA

#### **Sound Level vs Distance:**

Sound level decreases as the sound waves travel over distance, so it is important to note the specified distance when comparing sound levels. For example, if a buzzer measures 88 decibels (dB) at 30 cm, then it will measure:

97 dB @ 10 cm

82 dB @ 60 cm

78 dB @ 1 Meter

Mallory Sonalert has developed a tool to help convert sound levels depending on the distance. You can download the tool from our website: <a href="http://www.mallory-sonalert.com/PerformanceCurves/Sound%20Level%20Distance%20Conversion%2">http://www.mallory-sonalert.com/PerformanceCurves/Sound%20Level%20Distance%20Conversion%2</a> <a href="https://www.mallory-sonalert.com/PerformanceCurves/Sound%20Level%20Distance%20Conversion%2">https://www.mallory-sonalert.com/PerformanceCurves/Sound%20Level%20Distance%20Conversion%2</a> <a href="https://www.mallory-sonalert.com/PerformanceCurves/Sound%20Level%20Distance%20Conversion%2">https://www.mallory-sonalert.com/PerformanceCurves/Sound%20Level%20Distance%20Conversion%2</a> <a href="https://www.mallory-sonalert.com/PerformanceCurves/Sound%20Level%20Distance%20Conversion%2">https://www.mallory-sonalert.com/PerformanceCurves/Sound%20Level%20Distance%20Conversion%2">https://www.mallory-sonalert.com/PerformanceCurves/Sound%20Level%20Distance%20Conversion%2</a> <a href="https://www.mallory-sonalert.com/">https://www.mallory-sonalert.com/</a> <a href="https://www.mallory-sonalert.com/">https:

### **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Mallory Sonalert: MSR516NJR